



SSC Construction Contractor Safety Meeting

June 4, 2020



Construction Safety

SSC Construction Inspection Safety Findings/Stats

May 2020



Contact Info:



NASA Safety

Matthew Scott matthew.r.scott@nasa.gov 228-688-1537 Construction Safety

Donna Dubuisson donna.a.dubuisson@nasa.gov 228-688-1167 Construction Safety

Elizabeth Calantoni elizabeth.calantoni@nasa.gov 228-688-1804 B2 Test Stand Neil Toupin neil.s.toupin@nasa.gov 228-688-1109 A1 Test Stand

http://constructionsafety.ssc.nasa.gov/



Contact Info:



NASA Safety

Mike Rewis mike.j.rewis@nasa.gov 228-688-2663 Construction Safety

Frank Olinger milford.f.olinger@nasa.gov 228-688-1766 Construction Safety

Delton Rodriguez delton.s.rodriguez@nasa.gov 228-688-2499 Construction Safety

Ronnie Good ronald.w.good@nasa.gov 228-688-1487 Construction Safety

http://constructionsafety.ssc.nasa.gov/



Contact Info:



BASTION/SACOM Safety

Donald Smith, CHST donald.g.smith-1@nasa.gov 228-688-1085 phone 228-234-0639 Cell

John Lindsay, CSP john.d.lindsay@nasa.gov 228-688-2557 phone 288-688-3503 fax Mark Bridenbeck, TES mark.a.bridenbeck@nasa.gov 228-688-1732 phone 228-313-0188 Cell

Will Davis william.b.davis@nasa.gov 228-688-3193 phone 228-688-3503 fax

http://constructionsafety.ssc.nasa.gov/





Construction Safety Report: 01 May – 09 May 2020

Findings: 0

Level 1 Severity : 0

(Corrected on the spot)

Level 2 Severity : 0

(Corrective action documented)





Construction Safety Report: 10 May – 16 May 2020

Findings: 0

Level 1 Severity : 0

(Corrected on the spot)

Level 2 Severity : 0

(Corrective action documented)





Construction Safety Report: 17 May – 23 May 2020

Findings: 0

Level 1 Severity : 0

(Corrected on the spot)

Level 2 Severity : 0

(Corrective action documented)





Construction Safety Report: 24 May – 31 May 2020

Findings: 0

Level 1 Severity : 0

(Corrected on the spot)

Level 2 Severity : 0

(Corrective action documented)



HEAT STRESS

April 2019

Heat Stress

Heat stress occurs when the body produces or absorbs more heat than it can release; the body loses its ability to cool itself. On average, July and August are the hottest months in the Stennis Space Center area (weatherspark.com).

The average high temperature is about 90°F The average humidity is about 80%

In 2014 alone, 2,630 workers suffered from heat illness and 18 died from heat stroke and related causes. Heat illnesses and deaths <u>are</u> <u>preventable</u> (OSHA).

Prevention of heat stress illnesses and injuries is vital. Employers should provide training to workers such that they understand what heat stress is, how it affects health and safety, and how it can be prevented. Workers at greater risk of heat stress illnesses include those who are 65 years of age or older, not acclimated, are overweight, have heart or kidney disease, high blood pressure, are pregnant, or take medications.

Heat Rash (caused by excessive sweating)



Heat-Related Illnesses

And Their Signs and Symptoms

Heat Exhaustion (caused by loss of water and electrolytes through sweating)







Sweaty Skin



Weakness

in the second





Cramps Nausea/ Vomiting

Fast Heartbeat

Heat Stroke Signs (occurs when the body becomes unable to control its temperature/can cause death or permanent disability)









Convulsions



Red, Hot, Dry Skin High Body Confusion Temperature

Fainting

Stennis Space Center's Heat Stress Warning System

(the daily flag can be found near the bottom of the Stennis Space Center (SSC) portal page)

http://sscintranet.ssc.nasa.gov/

| Category | Flag | Heat Index | Intensity of Prolonged Exposure and/or Physical Activity |
|--------------------|------------------|---|---|
| Okay | \triangleright | Less than 80°F (< 27°C) | |
| Caution | | 80 - 90°F (27 - 32°C) | Fatigue possible with prolonged exposure and/or physical activity. |
| Extreme Caution | Þ | 90 - 105°F (32 - 41°C) | Sunstroke, muscle cramps, and/or heat exhaustion possible with prolonged exposure and/or physical activity. |
| Danger | | 105 - 129°F (41 - 54°C) | Sunstroke, muscle cramps, and/or heat exhaustion likely. Heat stroke possible with prolonged exposure and/or physical activity. |
| Extreme Danger | | 130°F or higher (54°C or higher) | Heat stroke or sunstroke likely |

Severe Weather Status

Lightning All Clear





LDS Radar Image [Enlarge]



Extreme Caution Heat Index: 93° F Flag Definitions

Credit: NWS

Forecast and Radar | Severe Weather Warning System | Daily Ozone Forecast | National Hurricane Center

When possible workers should avoid exposure to extreme heat, sun exposure, and high humidity.

When these exposures cannot be avoided, workers should take the following steps to prevent heat stress illnesses:

- Acclimate to hot work environments
- Educate workers and supervisors to recognize heat stress illnesses
- Wear light-colored, loose-fitting, breathable clothing such as cotton
- Take breaks in the shade or in a cool area when possible
- Drink water frequently (approximately 1 cup every 15-20 minutes)
- Monitor your physical condition and that of your coworkers
- Avoid alcohol and drinks with large amounts of caffeine or sugar
- Use the buddy system when working out, especially on runs, bike rides, etc.

In the Event of An Emergency at SSC:

Summon emergency medical services by dialing **911** from a SSC land line or dial (**228**) **688-3636** if using a cell phone.

While waiting for help to arrive:

Move the affected worker(s) to a cool, shaded area Loosen or remove heavy clothing Provide cool drinking water Fan and mist the worker with water



From SCWI-8715-0014, Heat Stress Section 5.4

- Fresh drinking water (plumbed, bottled, or water coolers) shall be provided daily at construction sites. If coolers are used, they shall be changed daily, taped/sealed, and dated. Wherever practical, fresh drinking water shall be cool, either by refrigeration or added ice.
- Water coolers shall be cleaned/sanitized as needed, <u>but no less</u> <u>than once per week</u> per the following guidance:
 - Wash, wipe and/or rinse the cooler with a detergent and water (wipe/wash away visible algae/grime/dirt).
 - Sanitize the water cooler with a chlorine-to-water mixture of 1:250 (1 tablespoon per gallon of water).
 - Sanitize all surfaces in contact with the drinking water.
 - Let it stand for two (2) minutes and then empty the cooler through the spigot to sanitize it.
 - The cooler can be air dried or rinsed with potable water.



QUESTIONS?







Discussion Topics

• Monthly Mishap Exposure Report

SSC Covid-19 Safe-at-Work Protocol Updates

https://sscsos.com

Questions?